


63-3-1

R-933




DAVIDSON LABORATORY

Report 933

WAVE-RESISTANCE REDUCTION
OF NEAR-SURFACE BODIES

by
King Eng and Pung N. Hu

March 1963



R-933

400 603

STEVENS INSTITUTE
OF TECHNOLOGY
CASTLE POINT STATION
HOBOKEN, NEW JERSEY

DAVIDSON LABORATORY
REPORT 933

March 1963


WAVE-RESISTANCE REDUCTION
OF NEAR-SURFACE BODIES

by
King Eng and Pung N. Hu

Prepared for .
Office of Naval Research
Contract Nonr 263(10)
(DL Project FX2531)

Reproduction in whole or in part is permitted
for any purpose of the United States Government

Approved


Dr. John Breslin
Director

ABSTRACT

An analytical study of the wave-resistance characteristics of near-surface bodies was conducted to determine 1) for a given length and displacement, what changes in body-surface geometry are necessary to cause wave-resistance reduction, and 2) how geometrical change affects the wave-resistance behavior with Froude number and submergence depth. The general wave-resistance expression for a perturbed ellipsoid with the constraints of constant displacement and length is formulated. A digital computer solution of this variational problem is obtained for the case of the spheroid due to available computer-size limitations.

The effects of fineness ratio and submergence-to-length ratio on the Froude number behavior of the wave resistance for a range of perturbations is demonstrated. Substantial reduction in wave resistance is possible for all Froude numbers above and slightly below the optimum Froude number for a particular perturbation distribution. For Froude numbers lower than approximately 10% below the optimum Froude number, a large increase in wave-resistance coefficient may be obtained depending upon the perturbation used. Since this generally occurs at low Froude numbers, the actual increase in total resistance experienced for perturbations yielding acceptable geometrical changes should be quite acceptable. Depending upon the optimum Froude number, the geometrical changes required for wave-resistance reduction fall into two classes: 1) midsection bulge with finer bow and stern for Froude numbers below 0.32; and 2) above 0.32 Froude number a midsection pinch with bulging bow and stern.

NOMENCLATURE

a_1, a_2, a_3	semi-axes of an ellipsoid
A, A_m	perturbation parameter
D	diameter of spheroid
e, \bar{e}	eccentricity of ellipse
$F = \frac{U}{gL}$	Froude number
g	acceleration of gravity
k_0	$\frac{g}{U^2}$
k_1	longitudinal added mass coefficient
r_0, r, r_1	radius
R_0, R	wave resistance
R_0', R', R_m'	wave-resistance coefficient
$-U$	constant uniform stream velocity
x_1, x_2, x_3	rectangular coordinates
ξ_1, ξ_2, ξ_3	rectangular coordinates
$\phi, \phi_0, \phi_1, \Phi$	velocity potential
μ, μ_0, μ_1	strength of doublets with axes in the positive x_1 -direction
$\bar{\mu}$	normalized strength of doublets with axes in the positive x_1 -direction
ρ	mass density of fluid
Subscript m denotes optimum value	

TABLE OF CONTENTS

	<u>Page</u>
Abstract	111
Nomenclature	1v
Introduction	1
Theory	2
Geometry of Perturbed Spheroid	12
Results and Analysis	13
Acknowledgments	15
References	16
Appendix	A-1
Figures	

INTRODUCTION

As an integral part of the research program on high-speed ship forms at Davidson Laboratory, an analytical investigation into the reduction of the wave resistance of a submerged body moving close to the water surface was conducted. The major problems of interest in the investigation were:

(1) For a given volume and length, how should the surface geometry be changed in order to cause a reduction in wave resistance?

(2) How does the geometrical change affect the wave-resistance behavior with Froude number and depth of immersion?

The linearized theory of wave resistance for bodies moving near the surface has been well established by Michell, Havelock, Lunde, etc. These theories impose a linearized free-surface boundary condition on the velocity potential. The wave-resistance expression is an integral with a quadratic integrand consisting either of functions that define the shape of the hull, or functions that define some type of hydrodynamic singularities by which the hull is generated. The latter type of integrand, being mathematically more tractable, is used in this study. The purpose here is to find a hull geometry of minimum wave resistance. Therefore, the investigation becomes a variational problem, and it is apparent that the variation should be in the hydrodynamic singularities.

Weinblum¹ treated such a minimum problem by considering a family of hull curves whose doublet distribution was expressed by polynomials having several arbitrary parameters. His result shows that, for a given Froude number and immersion depth, the doublet distribution and its

corresponding wave resistance can be evaluated in terms of a table of functions. However, no comparison can be made with his results because the hull displacement is not constrained.

The general case of a perturbed ellipsoid is considered in this analysis. It is approached as a variational problem with constant displacement as a subsidiary condition. The ellipsoid is represented by doublets distributed over the confocal ellipse. This doublet distribution is then perturbed such that the perturbation will have no influence on the volume of the ellipsoid, and will produce a new hull with less wave resistance.

THEORY

Throughout the discussion, the axes x_1 , x_2 and x_3 of a right-hand Cartesian coordinate system are fixed on the moving body. The origin O has been taken at the geometric center of the body with Ox_1 parallel to the direction of motion and Ox_3 vertically upward. The fluid is assumed to be incompressible and inviscid. The motion is irrotational and characterized by a velocity potential ϕ which defines the fluid velocity \bar{q} by $\bar{q} = -\nabla\phi$. The wave height on the free surface is taken to be small in comparison to the wave length.

Consider an ellipsoid with semi-axes $a_1 > a_2 > a_3$ moving in an infinite fluid at a constant speed U along the x_1 -direction. The velocity potential which describes the absolute motion of the fluid is given by²

$$\phi_0(x_1, x_2, x_3) = \iint_{\xi_3=0} \mu_0(\xi_1, \xi_2) \frac{\partial}{\partial \xi_1} \left(\frac{1}{r} \right) d\xi_1 d\xi_2 \quad (1)$$

where

$$\mu_0(\xi_1, \xi_2) = \frac{UD_1}{\pi} \left[1 - \left(\frac{\xi_1}{a_1 e} \right)^2 - \left(\frac{\xi_2}{a_2 \bar{e}} \right)^2 \right]^{1/2} \quad (2)$$

$$e^2 = 1 - \left(\frac{a_3}{a_1} \right)^2 \quad (3)$$

$$\bar{e}^2 = 1 - \left(\frac{a_3}{a_2} \right)^2 \quad (4)$$

$$D_1 = \frac{a_3}{(2-a_1) e \bar{e}} \quad (5)$$

$$a_1 = a_1 a_2 a_3 \int_0^\infty \frac{d\lambda}{(a_1^2 + \lambda) \sqrt{(a_1^2 + \lambda)(a_2^2 + \lambda)(a_3^2 + \lambda)}} \quad (6)$$

$$r^2 = (x_1 - \xi_1)^2 + (x_2 - \xi_2)^2 + (x_3 - \xi_3)^2 \quad (7)$$

The surface integral in eq. 1 is taken over the confocal ellipse

$$\left(\frac{\xi_1}{a_1 e} \right)^2 + \left(\frac{\xi_2}{a_2 \bar{e}} \right)^2 = 1 \quad (8)$$

on the plane $\xi_3 = 0$. Let the ellipsoid be perturbed such that the perturbation can be represented by a doublet distribution $\mu_1(\xi_1, \xi_2)$ in addition to the original doublet distribution $\mu_0(\xi_1, \xi_2)$. $\mu_1(\xi_1, \xi_2)$ is bounded by the same confocal ellipse given by eq. 8. The perturbation potential is then

$$\phi_1(x_1, x_2, x_3) = \iint_{\xi_3=0} \mu_1(\xi_1, \xi_2) \frac{\partial}{\partial \xi_1} \left(\frac{1}{r} \right) d\xi_1 d\xi_2 \quad (9)$$

The resultant potential for the perturbed ellipsoid becomes

$$\phi(x_1, x_2, x_3) = \iint_{\xi_3=0} \mu(\xi_1, \xi_2) \frac{\partial}{\partial \xi_1} \left(\frac{1}{r} \right) d\xi_1 d\xi_2 \quad (10a)$$

$$\text{where } \phi(x_1, x_2, x_3) = \phi_0(x_1, x_2, x_3) + \phi_1(x_1, x_2, x_3) \quad (10b)$$

$$\text{and } \mu(\xi_1, \xi_2) = \mu_0(\xi_1, \xi_2) + \mu_1(\xi_1, \xi_2) \quad (10c)$$

is the resultant doublet distribution. It is required that the volume remains constant upon this perturbation; therefore,*

$$\oint_{\xi_3=0} \mu_1(\xi_1, \xi_2) d\xi_1 d\xi_2 = 0 \quad (11)$$

By letting $\mu_1(\xi_1, \xi_2) = \mu_0(\xi_1, \xi_2)Q$, where $Q = Q(\xi_1, \xi_2)$

is an arbitrary function to be chosen later, eq. 10 becomes

$$\phi(x_1, x_2, x_3) = \frac{UD_1}{\pi} \oint_{\xi_3=0} \left[1 - \left(\frac{\xi_1}{a_1 e} \right)^2 - \left(\frac{\xi_2}{a_2 e} \right)^2 \right]^{\frac{1}{2}} (1+Q) \frac{\partial}{\partial \xi_1} \left(\frac{1}{r} \right) d\xi_1 d\xi_2 \quad (12)$$

* According to Taylor's added mass theorem,

$U\rho V(1+k_1) = 4\pi\rho \oint (\mu_0 + \mu_1) d\xi_1 d\xi_2 = U\rho V_0(1+k_1^0) + 4\pi\rho \oint \mu_1 d\xi_1 d\xi_2$
where k_1 , V and k_1^0 , V_0 are longitudinal added mass coefficient and volume of the perturbed and unperturbed ellipsoid, respectively.

$$\text{Then } V(1+k_1) - V_0(1+k_1^0) = \frac{4\pi}{U} \oint \mu_1 d\xi_1 d\xi_2 = 0 \text{ by eq. 11}$$

$$\text{or } V = V_0 \left(\frac{1+k_1^0}{1+k_1} \right)$$

For elongated bodies of approximately same length and L/D , k_1 and k_1^0 are small in comparison to unity; also they are of the same order of magnitude, i.e, $k_1 - k_1^0$ is very small. Therefore,

$$\frac{1+k_1^0}{1+k_1} \div 1 \text{ or } V \div V_0$$

When the body is moving below a free surface, the velocity potential must satisfy the linearized boundary condition

$$\frac{\partial^2 \phi}{\partial x_1^2} + k_0 \frac{\partial \phi}{\partial x_3} = 0 \quad (13)$$

where $k_0 = \frac{g}{U^2}$

on the free surface ($x_3 = f$).

The Green's function, satisfying this condition (eq. 13), is given by ^{5,8}

$$G(x_1, x_2, x_3; \xi_1, \xi_2, \xi_3) = \frac{1}{r} - \frac{1}{r_1} - \frac{4k_0}{\pi} \operatorname{Re} \int_0^{\frac{\pi}{2}} \int_0^{\infty} \sec^2 \theta \cdot e^{k[(x_3 + \xi_3 - 2f) + 1(x_1 - \xi_1) \cos \theta]} \frac{\cos[k(x_2 - \xi_2) \sin \theta]}{k - k_0 \sec^2 \theta} dk d\theta \quad (14)$$

where $r_1^2 = (x_1 - \xi_1)^2 + (x_2 - \xi_2)^2 + (x_3 + \xi_3 - 2f)^2$

Physically, the Green's function represents the velocity potential of a source moving at a depth f below the free surface. Therefore, to a first-order approximation, the velocity potential of the body, represented by the doublet distribution $\mu(\xi_1, \xi_2)$, moving below a free surface may be expressed as

$$\phi = \phi(x_1, x_2, x_3) = \iint_{\xi_3=0} \mu(\xi_1, \xi_2) \frac{\partial G}{\partial \xi_1} d\xi_1 d\xi_2 \quad (15)$$

Substituting eq. 14 into eq. 15, the potential ϕ for $(x_1 - \xi_1) > 0$ and $(x_1 - \xi_1) < 0$ becomes, respectively,

$$\Phi = \iint \mu(\xi_1, \xi_2) (x_1 - \xi_1) \left(\frac{1}{r^3} - \frac{1}{r_1^3} \right) d\xi_1 d\xi_2$$

$$- \frac{4k_0}{\pi} \operatorname{Im} \iint \mu(\xi_1, \xi_2) \int_0^{\frac{\pi}{2}} \int_0^{\infty} \frac{k \sec \theta}{k - k_0 \sec^2 \theta} \cos [k(x_2 - \xi_2) \sin \theta]$$

$$e^{k[(x_3 - 2f) + 1(x_1 - \xi_1) \cos \theta]} d\xi_1 d\xi_2 dk d\theta$$

and $\Phi = \iint \mu(\xi_1, \xi_2) (x_1 - \xi_1) \left(\frac{1}{r^3} - \frac{1}{r_1^3} \right) d\xi_1 d\xi_2$

$$- \frac{4k_0}{\pi} \operatorname{Im} \iint \mu(\xi_1, \xi_2) \int_0^{\frac{\pi}{2}} \int_0^{\infty} \frac{k \sec \theta}{k + k_0 \sec^2 \theta} \cos [k(x_2 - \xi_2) \sin \theta]$$

$$e^{-k[(x_3 - 2f) + 1 |x_1 - \xi_1| \cos \theta]} d\xi_1 d\xi_2 dk d\theta$$

$$+ 8k_0^2 \int_0^{\frac{\pi}{2}} \iint \mu(\xi_1, \xi_2) \cos [k_0(x_1 - \xi_1) \sec \theta] \cdot \cos [k_0(x_2 - \xi_2)$$

$$\sec^2 \theta \sin \theta] \sec^3 \theta e^{k_0(x_3 - 2f) \sec^2 \theta} d\xi_1 d\xi_2 d\theta$$

From ref. 6, the wave-resistance expression derived from a consideration of the energy expended in the production of waves is given as

$$R = \frac{\rho}{2k_0} \int_{-\infty}^{\infty} \left[\left(\frac{\partial \Phi}{\partial x_1} \right)^2 - \Phi \frac{\partial^2 \Phi}{\partial x_1^2} \right]_{x_3=f} dx_2 - \frac{\rho}{2} \int_{-\infty}^f \int_{-\infty}^{\infty} \left[\left(\frac{\partial \Phi}{\partial x_1} \right)^2 - \Phi \frac{\partial^2 \Phi}{\partial x_1^2} \right]_{x_1 \rightarrow -\infty} dx_2 dx_3 \quad (16)$$

From ref. 5, the velocity potential of Φ at $x_1 \rightarrow -\infty$ can be approximated to the form

$$\Phi \Big|_{x_1 \rightarrow -\infty} = 8k_0^2 \int_0^{\pi/2} \iint \mu(\xi_1, \xi_2) \cos q_1 \left(\frac{x_1 - \xi_1}{a_1 e} \right) \cos q_2 \left(\frac{x_2 - \xi_2}{a_2 \bar{e}} \right) \sec^3 \theta \cdot e^{k_0(x_3 - 2f) \sec^2 \theta} d\xi_1 d\xi_2 d\theta \quad (17)$$

where $q_1 = k_0 a_1 e \sec \theta$; $q_2 = k_0 a_2 \bar{e} \sec^2 \theta \sin \theta$.

Substituting eq. 17 into eq. 16, one gets:

$$R = 16\pi\rho k_0^4 \int_0^{\pi/2} (P_1^2 + P_2^2 + P_3^2 + P_4^2) \sec^5 \theta e^{-2k_0 f \sec^2 \theta} d\theta \quad (18)$$

where

$$P_1 = \iint \mu(\xi_1, \xi_2) \cos q_1 \left(\frac{\xi_1}{a_1 e} \right) \cos q_2 \left(\frac{\xi_2}{a_2 \bar{e}} \right) d\xi_1 d\xi_2 \quad (19a)$$

$$P_2 = \iint \mu(\xi_1, \xi_2) \sin q_1 \left(\frac{\xi_1}{a_1 e} \right) \cos q_2 \left(\frac{\xi_2}{a_2 \bar{e}} \right) d\xi_1 d\xi_2 \quad (19b)$$

$$P_3 = \iint \mu(\xi_1, \xi_2) \sin q_1 \left(\frac{\xi_1}{a_1 e} \right) \sin q_2 \left(\frac{\xi_2}{a_2 \bar{e}} \right) d\xi_1 d\xi_2 \quad (19c)$$

$$P_4 = \iint \mu(\xi_1, \xi_2) \cos q_1 \left(\frac{\xi_1}{a_1 e} \right) \sin q_2 \left(\frac{\xi_2}{a_2 \bar{e}} \right) d\xi_1 d\xi_2 \quad (19d)$$

The P_1^2 terms in eq. 18 are all positive definite quantities. Therefore, each P_1^2 term will contribute to wave resistance. However, if $\mu(\xi_1, \xi_2)$ is an even function with respect to ξ_1 and ξ_2 , i.e., $\mu(\xi_1, \xi_2) = \mu(-\xi_1, -\xi_2)$, then P_2 , P_3 and P_4 vanish identically which to some extent reduces the resistance R . As a result, doubly-symmetric bodies are better forms as far as wave resistance is concerned.

Consequently, the expression of the doublet distribution takes the form:

$$\mu(\xi_1, \xi_2) = \frac{UD_1}{\pi} \left[1 - \left(\frac{\xi_1}{a_1 e} \right)^2 - \left(\frac{\xi_2}{a_2 e} \right)^2 \right]^{1/2} (1 + Q)$$

Q will be chosen as an even function with respect to ξ_1 and ξ_2 . Obviously, the choice of Q is not unique under these constraints. For the sake of mathematical simplicity, the choice of Q for the present study is

$$Q(\xi_1, \xi_2) = -A \cos \lambda \left(\frac{\xi_1}{a_1 e} \right) \cos \nu \left(\frac{\xi_2}{a_2 e} \right) \quad (20)$$

where A, λ and ν are arbitrary parameters to be determined. The doublet distribution expression now takes the form

$$\mu(\xi_1, \xi_2) = \frac{UD_1}{\pi} \left[1 - \left(\frac{\xi_1}{a_1 e} \right)^2 - \left(\frac{\xi_2}{a_2 e} \right)^2 \right]^{1/2} \left[1 - A \cos \lambda \left(\frac{\xi_1}{a_1 e} \right) \cos \nu \left(\frac{\xi_2}{a_2 e} \right) \right] \quad (21)$$

Substituting eq. 20 into the constraint equation (eq. 11), one obtains

$$-\left(\frac{UD_1}{\pi} \right) A \iint \left[1 - \left(\frac{\xi_1}{a_1 e} \right)^2 - \left(\frac{\xi_2}{a_2 e} \right)^2 \right]^{1/2} \cos \lambda \left(\frac{\xi_1}{a_1 e} \right) \cos \nu \left(\frac{\xi_2}{a_2 e} \right) d\xi_1 d\xi_2 = 0$$

which can be satisfied if (see Appendix)

$$A(\sqrt{\lambda^2 + \nu^2})^{-3/2} J_{3/2}(\sqrt{\lambda^2 + \nu^2}) = 0$$

For nontrivial solution of A, λ and ν , one has

$$\sqrt{\lambda^2 + \nu^2} = \tan \sqrt{\lambda^2 + \nu^2} \quad (22)$$

Substituting eq. 21 into eqs. 19a through 19d, the results are (see Appendix)

$$P_1 = UD_1 (\psi_0 - A\psi) \quad (23)$$

$$P_2 = 0, P_3 = 0, \text{ and } P_4 = 0 \quad (24)$$

where

$$\psi_0 = 2\sqrt{\frac{\pi}{2}} \frac{J_{3/2}(\sqrt{q_1^2 + q_2^2})}{(\sqrt{q_1^2 + q_2^2})^{3/2}} ; \bar{D}_1 = \frac{a_1 a_2 a_3}{(2 - a_1)}$$

$$\psi = \frac{1}{2}\sqrt{\frac{\pi}{2}} \left\{ \frac{J_{3/2}(\sqrt{(\lambda-q_1)^2 + (\nu-q_2)^2})}{(\sqrt{(\lambda-q_1)^2 + (\nu-q_2)^2})^{3/2}} + \frac{J_{3/2}(\sqrt{(\lambda-q_1)^2 + (\nu+q_2)^2})}{(\sqrt{(\lambda-q_1)^2 + (\nu+q_2)^2})^{3/2}} + \right. \\ \left. \frac{J_{3/2}(\sqrt{(\lambda+q_1)^2 + (\nu-q_2)^2})}{(\sqrt{(\lambda+q_1)^2 + (\nu-q_2)^2})^{3/2}} + \frac{J_{3/2}(\sqrt{(\lambda+q_1)^2 + (\nu+q_2)^2})}{(\sqrt{(\lambda+q_1)^2 + (\nu+q_2)^2})^{3/2}} \right\}$$

$$\text{and } q_1 = k_0 a_1 e \sec \theta ; q_2 = k_0 a_2 \bar{e} \sec^2 \theta \sin \theta$$

Substituting eq. 23 into eq. 18, R becomes

$$R = 16\pi\rho k_0^4 (\bar{U}\bar{D}_1)^2 \int_0^{\pi/2} (\psi_0 - A\psi)^2 g(\theta) d\theta \quad (25)$$

$$\text{where } g(\theta) = \sec^5 \theta e^{-k_0 f \sec^2 \theta}$$

$$\text{Let } L = 2a_1, F^2 = \frac{U^2}{gL} = \frac{1}{2k_0 a_1}, \text{ and } R' = \frac{R}{\frac{1}{2} \rho U^2 L^2}$$

where F is the Froude number, and R' is the wave resistance coefficient. Then

$$R' = K \int_0^{\pi/2} (\psi_0 - A\psi)^2 g(\theta) d\theta \quad (26)$$

$$\text{where } K = \frac{\pi}{2} \left(\frac{1 - e^2}{2 - \alpha_1} \right) \frac{1}{(1 - \bar{e}^2)} \frac{1}{F^3}$$

Denoting

$$R_0 = K \int_0^{\frac{\pi}{2}} \psi_0^2 g(\theta) d\theta \quad (27a)$$

$$R_1 = K \int_0^{\frac{\pi}{2}} \psi \psi_0 g(\theta) d\theta \quad (27b)$$

$$\text{and } R_2 = K \int_0^{\frac{\pi}{2}} \psi^2 g(\theta) d\theta \quad (27c)$$

R' can be written in terms of a perturbation parameter A^* as follows:

$$R'(A) = R_0 - 2AR_1 + A^2R_2 \quad (28)$$

The first and second variations of $R'(A)$ are given, respectively, as

$$\delta R'(A) = 2(-R_1 + AR_2) \delta A \quad (29)$$

and

$$\delta^2 R'(A) = 2R_2 (\delta A)^2 \quad (30)$$

since R_2 is positive definite as seen from eq. 27c, eq. 30 shows that if $R'(A)$ has an extremal, it is a minimum. The minimum of R' occurs at

$$A = A_m = \frac{R_1^{**}}{R_2} \quad (31)$$

and has a value

$$R'(A_m) = R'_m = R_0 - \frac{R_1^2}{R_2} \quad (32)$$

* R is also a function of λ and ν , but the major parameter which reduces wave resistance is the parameter A .
 **Since $R_1 = R_1(\lambda, \nu)$ and $R_2 = R_2(\lambda, \nu)$, therefore $A_m = A_m(\lambda, \nu) = \frac{R_1(\lambda, \nu)}{R_2(\lambda, \nu)}$, then for various values of (λ, ν) that satisfy eq. 31 and the constraint condition eq. 22, a family of hull forms of similar wave-resistance characteristics will result.

Since it is not possible to obtain a closed form solution of R_0 , R_1 and R_2 , the problem solution requires the use of a large capacity digital computer. Due to the limited capacity and speed of Stevens Institute's 1620 IBM computer, numerical results are presented only for the general case of a perturbed spheroid.

The equations of a perturbed spheroid can be obtained by taking limits of the perturbed ellipsoid equations, i.e., let $n = 0$, $\xi_2 \rightarrow 0$ and $\bar{e} \rightarrow 0$. The spheroid equations then become for doublet strength:

$$\mu(\xi) = \frac{U(a_1 e)^2}{2 \left[\frac{2e}{1-e^2} - \ln \left(\frac{1+e}{1-e} \right) \right]} (1 - \xi^2) (1 - A \cos \lambda \xi) \quad (33)$$

where $\xi = \frac{\xi_1}{a_1 e}$ and $-1 \leq \xi \leq 1$,

and for the potential in an infinite fluid:

$$\Phi(\xi) = \int_{-1}^1 \mu(\xi) \frac{\partial}{\partial \xi} \left(\frac{1}{r} \right) d\xi \quad (34)$$

where $r^2 = (x_1 - a_1 e \xi)^2 + y^2$; $y^2 = x_2^2 + x_3^2$.

The characteristic equation resulting from the constant volume constraint reduces to:

$$\lambda = \tan \lambda. \quad (35)$$

The expressions R_0 , R_1 , R_2 , R' , A_m and R'_m remain unchanged, but K , ψ_0 and ψ are different.

$$R_0 = K \int_0^{\frac{\pi}{2}} \psi_0^2 g(\theta) d\theta \quad (36a)$$

$$R_1 = K \int_0^{\frac{\pi}{2}} \psi \psi_0 g(\theta) d\theta \quad (36b)$$

$$R_2 = K \int_0^{\pi/2} \psi^2 g(\theta) d\theta \quad (36c)$$

$$R' = R_0 - 2AR_1 + A^2R_2 \quad (37)$$

$$A_m = \frac{R_1}{R_2} \quad (38)$$

$$R'_m = R_0 - \frac{R_1^2}{R_2} \quad (39)$$

$$K = \frac{\pi}{2} \left\{ \frac{e^3}{F^4 \left[\frac{2e}{1-e^2} - \ln\left(\frac{1+e}{1-e}\right) \right]} \right\}^2$$

$$\psi_0 = \frac{2}{q_1^3} (\sin q_1 - q_1 \cos q_1)$$

$$\psi = \frac{\sin(\lambda - q_1) - (\lambda - q_1) \cos(\lambda - q_1)}{(\lambda - q_1)^3} + \frac{\sin(\lambda + q_1) - (\lambda + q_1) \cos(\lambda + q_1)}{(\lambda + q_1)^3}$$

$$\text{where } q_1 = \frac{e}{2F^2} \sec \theta.$$

GEOMETRY OF PERTURBED SPHEROID*

The doublet distribution between foci

$$\mu_0(\xi) = \frac{Ua_1^2 e^2 (1 - \xi^2)}{2 \left[\frac{2e}{1-e^2} - \ln\left(\frac{1+e}{1-e}\right) \right]}, \quad \xi = \frac{x}{a_1 e} \quad (40)$$

is the image of the uniform stream $-U$ within the spheroid:

$$r_0^2 = a_1^2 (1 - e^2) (1 - e^2 \xi^2) \quad (41)$$

* This method is suggested by Professor L. Landweber, from the State University of Iowa.

An increment in the doublet distribution $\Delta\mu$ will produce a change in the ordinate of the spheroid which, it will be assumed, is given by modified Munk's formula:

$$\Delta\mu = \frac{1 + k_1}{4} U\Delta(r^2) \quad (42)$$

where k_1 is the added mass coefficient of the spheroid given by¹²

$$\frac{2}{1+k_1} = \frac{1-e^2}{e^3} \left[\frac{2e}{1-e^2} - \ln\left(\frac{1+e}{1-e}\right) \right] \quad (43)$$

Taking $\Delta\mu = \mu_1 = -A\mu_0(\xi)\cos\lambda\xi$, together with eqs. 40, 42 and 43:

$$\Delta(r^2) = -\frac{Aa_1^2(1-e^2)}{e} (1-\xi^2) \cos\lambda\xi \quad (44)$$

combine eqs. 41 and 44 and get:

$$r^2(\xi) = r_0^2 + \delta(r^2) = a_1^2(1-e^2) \left[1 - e^2\xi^2 - \frac{A}{e}(1-\xi^2)\cos\lambda\xi \right] \quad (45)$$

$$r(x) = \left(\frac{D}{L}\right) \sqrt{1 - \left(\frac{x}{a_1}\right)^2 - \frac{A}{e^3} \left[e^2 - \left(\frac{x}{a_1}\right)^2 \right] \cos \frac{\lambda}{e} \left(\frac{x}{a_1}\right)} \quad (46)$$

where $r(x)$ is the radius of the perturbed spheroid along the x-axis

$\left(\frac{D}{L}\right)$ is the slenderness ration of the undisturbed spheroid.

RESULTS AND ANALYSIS

The optimum perturbation parameter A_m is plotted versus Froude number in Fig. 1. At Froude numbers below .30, A_m is almost independent of both slenderness and immersion ratio. For Froude numbers $.28 < F < .30$, A_m shows little change and has a value of approximately $A_m = -.20$. For $F > .30$, A_m

varies significantly with depth, f/L , but varies very little with fineness ratio, D/L . This result is expected because at infinite depth, there is no wave resistance.

By examining the doublet distribution, one can obtain a good indication of what the approximate hull form will be like. Therefore, from eq. 33, one may conclude that:

- 1) for $A < 0$, the hull forms bulge out at the midsection and are narrow at the ends,
- 2) for $0 < A < 1$, the hull forms neck in at the midsection and bulge out at the ends,
- 3) for $A > 1$, the hull form may be imaginary.

There is no clear-cut dividing line as to what type of body geometry a hull may have and still be considered reasonable. However, the perturbed bodies with $A < 0.5$ generated from a spheroid could easily be considered reasonable forms.

The fact that the body geometry for minimum wave resistance varies with Froude number and immersion ratio makes it apparent that there is no single hull that can have minimum wave resistance over a range of Froude numbers and submergence depths. However, from Fig. 1 and eq. 33, for arbitrary values of A ranging from $-0.20 < A < 1$, there is associated a hull form which will have a minimum at some F and f/L . For example: for $A = -0.20$, the minimum will occur between $F = 0.28$ and 0.30 . With this in mind, $A = -0.20, 0.25, 0.50$ and 0.75 were chosen to illustrate the results of this analysis. The Froude number and submergence ratio corresponding to the minimum for the above perturbation parameters are shown in Fig. 2. The associated normalized doublet distributions and the approximate hull form are shown respectively in Figs. 3 and 4.

Figures 5 and 6, respectively, show the wave-resistance variation with Froude number and immersion ratio. As

would be expected, the wave resistance over the entire Froude-number range is affected by the geometrical change resulting from the perturbation. For $A > 0$ the wave-resistance coefficient, in general, has a reduction at high Froude-number values, but shows considerable increase at low values, especially when the body moves toward the free surface. Also, for $A < 0$, the wave-resistance coefficient reduces at low but increases at high Froude numbers.

ACKNOWLEDGMENTS

The authors wish to acknowledge their gratitude to Professor L. Landweber, consultant for Davidson Laboratory and Mr. Earl Uram, staff scientist at the laboratory, for their suggestions and review of this report.

REFERENCES

1. Weinblum, G.P.: "The Wave Resistance of Bodies of Revolution," DTMB Report 758, May 1951.
2. Newman, J.N.: "The Damping of an Oscillating Ellipsoid Near a Free Surface," Jour. of Ship Research, Vol. 5, No. 3, December 1961.
3. Havelock, T.H.: "The Wave Resistance of an Ellipsoid," Proceedings of the Royal Society, A, Volume 132, 1931, pp. 480-486.
4. Havelock, T.H.: "The Wave Resistance of a Spheroid," Proc. of the Royal Society, A, Vol. 131, 1931, pp. 275-285.
5. Havelock, T.H.: "Wave Resistance Theory and its Application to Ship Problems," Trans. SNAME, Vol. 59, 1951, pp. 13-24.
6. Lunde, J.K.: "On the Theory of Wave Resistance and Wave Profile," Skipsmodelltankens Meddelelse NR. 10, April 1952.
7. Lunde, J.K.: "On the Linearized Theory of Wave Resistance for Displacement Ships in Steady and Accelerated Motion," Trans. SNAME, Vol. 59, 1952, pp. 25-76.
8. Peters, A.S. and Stoker, J.J.: "The Motion of a Ship, as a Floating Rigid Body, in a Seaway," Communications on Pure and Applied Mathematics, Volume X, No. 3, August 1957.
9. Karp, S., Kotik, J. and Lurye, J.: "On the Problem of Wave Resistance for Struts and Strut-Like Dipole Distributions," Proceedings of the Third Symposium on Naval Hydrodynamics, October 19-22, 1962, Scheveningen, Holland.
10. Pond, H.L.: "The Pitching Moment Acting on a Body of Revolution Moving Under a Free Surface," DTMB Report 819, May 1952.
11. Pond, H.L.: "The Moment Acting on a Rankine Ovoid Moving Under a Free Surface," DTMB Report 429, September 1951.
12. Lamb, H.: Hydrodynamics, 6th Edition, Cambridge Univ. Press, England, 1940.
13. Watson, G.N.: "Theory of Bessel Functions," 2nd Edition, 1952.

APPENDIX

Evaluate the surface integral of the form

$$I = \iint \sqrt{1 - \left(\frac{x}{a}\right)^2 - \left(\frac{y}{b}\right)^2} \cos \alpha x \cos \beta y dx dy$$

over the surface of an ellipse

$$\left(\frac{x}{a}\right)^2 + \left(\frac{y}{b}\right)^2 = 1$$

where a and b are arbitrary constants.

Let $x = a \sin \phi \cos \theta$ and $y = b \cos \phi$, then the element surface becomes $ds = ab \sin^2 \phi \sin \theta d\phi d\theta$.

Upon change of variables, the integral I can be written as

$$I = ab \int_0^\pi \int_0^\pi \sin^3 \phi \sin^2 \theta \cos \left[(a \sin \phi) \cos \theta \right] \cos (b \cos \phi) d\theta d\phi.$$

Denoting $\gamma = a \sin \phi$, and integrating with respect to θ :

$$\begin{aligned} P(\gamma) &= \int_0^\pi \sin^2 \theta \cos(\gamma \cos \theta) d\theta \\ &= -\frac{1}{\gamma} \int_0^\pi \sin \theta \cos(\gamma \cos \theta) d(\gamma \cos \theta). \end{aligned}$$

Integrating $P(\gamma)$ by parts, we obtain

$$P(\gamma) = \frac{1}{\gamma} \int_0^\pi \cos \theta \sin(\gamma \cos \theta) d\theta = \frac{\pi}{\gamma} J_1(\gamma).$$

Substitute $P(\gamma)$ back into I ; then I becomes

$$I = \frac{\pi b}{a} \int_0^\pi \sin^2 \phi J_1(a \sin \phi) \cos(b \cos \phi) d\phi$$


$$\text{but } \cos \phi = \sqrt{\frac{\pi \delta}{2}} J_{-\frac{1}{2}}(\delta)$$

therefore

$$I = \frac{\pi\sqrt{2\pi b\beta}}{a} \int_0^{\pi} J_1(a\sin\phi) J_{-\frac{1}{2}}(b\beta\cos\phi) \cos^{\frac{1}{2}}\phi \sin^2\phi d\phi .$$

From ref. 13, under Sonine's second finite integral, the expression I is of the form

$$I = (\pi\sqrt{2\pi ab}) \frac{J_{3/2}(\sqrt{(a\alpha)^2 + (b\beta)^2})}{(\sqrt{(a\alpha)^2 + (b\beta)^2})^{3/2}} .$$



R-933

FIGURE 1. OPTIMUM PERTURBATION PARAMETER VS FROUDE NUMBER.




FIGURE 2. MINIMUM WAVE RESISTANCE OF THREE PERTURBED SPHEROID AS A FUNCTION OF FROUDE NUMBER AND IMMERSION RATIO.




FIGURE 3. NORMALIZED DOUBLET DISTRIBUTION, $\bar{\mu}(\xi)$.

SPHEROID SLENDERNESS RATIO $L/D=5$




FIGURE 4. CONFIGURATION OF PERTURBED SPHEROID




FIGURE 5. WAVE RESISTANCE COEFFICIENT OF PERTURBED SPHEROID VS FROUDE NUMBER.




FIGURE 6. WAVE RESISTANCE COEFFICIENT OF PERTURBED SPHEROID VS FROUDE NUMBER.

DISTRIBUTION LIST

Copies

<p>6 Chief of Naval Research Department of the Navy Washington 25, D. C. Attn: Codes 438 (3) 461 (1) 463 (1) 466 (1)</p> <p>1 Commanding Officer Office of Naval Research Branch Office 495 Summer Street Boston 10, Massachusetts</p> <p>1 Commanding Officer Office of Naval Research Branch Office 207 West 24th Street New York 11, New York</p> <p>1 Commanding Officer Office of Naval Research Branch Office 1030 East Green Street Pasadena, California</p> <p>1 Commanding Officer Office of Naval Research Branch Office 1000 Geary Street San Francisco 9, California</p> <p>25 Commanding Officer Office of Naval Research Branch Office Box 39, Navy # 100 Fleet Post Office New York, New York</p> <p>6 Director Naval Research Laboratory Washington 25, D. C. Attn: Code 2027</p> <p>5 Chief, Bureau of Naval Weapons Department of the Navy Washington 25, D. C. Attn: Codes RUAW-4 RRRE RAAD RAAD-222 DIS-42</p>	<p>8 Chief, Bureau of Ships Department of the Navy Washington 25, D. C. Attn: Codes 310 312 335 420 421 440 442 449</p> <p>1 Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D. C. Attn: Code D-400</p> <p>1 Commander U. S. Naval Ordnance Test Station China Lake, California Attn: Code 753</p> <p>2 Commander U. S. Naval Ordnance Test Station Pasadena Annex 3202 E. Foothill Blvd. Pasadena 8, California Attn: Code P-508</p> <p>1 Commander Planning Department Portsmouth Naval Shipyard Portsmouth, New Hampshire</p> <p>1 Commander Planning Department Boston Naval Shipyard Boston 29, Massachusetts</p> <p>1 Commander Planning Department Pearl Harbor Naval Shipyard Navy #128, Fleet Post Office San Francisco, California</p> <p>1 Commander Planning Department San Francisco Naval Shipyard San Francisco 24, California</p> <p>1 Commander Planning Department Mare Island Naval Shipyard Vallejo, California</p>
--	--

DISTRIBUTION LIST

Copies

- | | |
|--|---|
| <p>1 Director Eng. Sciences Div.
National Science Foundation
1951 Constitution Avenue, N.W.
Washington 25, D. C.</p> | <p>2 State University of Iowa
Iowa Institute of Hydraulic Research
Iowa City, Iowa
Attn: Dr. H. Rouse
Dr. L. Landweber</p> |
| <p>3 Director
National Bureau of Standards
Washington 25, D. C.
Attn: Fluid Mechanics Division
(Dr. G. B. Schubauer)
Dr. G. H. Keulegan
Dr. J. M. Franklin</p> | <p>2 Harvard University
Cambridge 38, Massachusetts
Attn: Professor G. Birkhoff
(Dept. of Mathematics)
Professor G. F. Carrier
(Dept. of Mathematics)</p> |
| <p>10 Armed Services Technical
Information Agency
Arlington Hall Station
Arlington 12, Virginia</p> | <p>2 Massachusetts Institute of Technology
Cambridge 39, Massachusetts
Attn: Department of Naval Architec-
ture and Marine Eng.
Professor A. T. Ippen</p> |
| <p>1 Office of Technical Services
Department of Commerce
Washington 25, D. C.</p> | <p>3 University of Michigan
Ann Arbor, Michigan
Attn: Professor R. B. Couch
(Dept. of Naval Arch.)
Professor W. W. Willmarth
(Aero. Engrg. Department)
Professor M. S. Uberoi
(Aero. Engrg. Department)</p> |
| <p>3 California Institute of Technology
Pasadena 4, California
Attn: Professor M. S. Plesset
Professor T. Y. Wu
Professor A. J. Acosta</p> | <p>3 Dr. L. G. Straub, Director
St. Anthony Falls Hydraulic Lab.
University of Minnesota
Minneapolis 14, Minnesota
Attn: Mr. J. N. Wetzel
Prof. B. Silberman</p> |
| <p>1 University of California
Department of Engineering
Los Angeles 24, California
Attn: Dr. A. Powell</p> | <p>1 Professor J. J. Foody
Engineering Department
New York State Univ. Maritime College
Fort Schulyer, New York</p> |
| <p>1 Director
Scripps Institute of Oceanography
University of California
La Jolla, California</p> | <p>2 New York University
Inst. of Mathematical Sciences
25 Waverly Place
New York 3, N. Y.
Attn: Prof. J. Keller
Prof. J. J. Stoker</p> |
| <p>1 Professor M. L. Albertson
Department of Civil Engineering
Colorado A&M College
Fort Collins, Colorado</p> | <p>3 The Johns Hopkins University
Department of Mechanical Engineering
Baltimore 18, Maryland
Attn: Prof. S. Corrsin (1)
Prof. O. M. Phillips (2)</p> |
| <p>1 Professor J. E. Cermak
Department of Civil Engineering
Colorado State University
Fort Collins, Colorado</p> | |
| <p>1 Professor W. R. Sears
Graduate School of Aeronautical
Engineering
Cornell University
Ithaca, New York</p> | |

DISTRIBUTION LIST

Copies

1 Commander Planning Department New York Naval Shipyard Brooklyn 1, New York	1 Commandant U. S. Coast Guard 1300 E. Street, N. W. Washington, D. C.
1 Commander Planning Department Puget Sound Naval Shipyard Bremerton, Washington	1 Secretary Ship Structure Committee U. S. Coast Guard Headquarters 1300 E. Street, N. W. Washington, D. C.
1 Commander Planning Department Philadelphia Naval Shipyard U. S. Naval Base Philadelphia 12, Pennsylvania	1 Commander Military Sea Transportation Service Department of the Navy Washington 25, D. C.
1 Commander Planning Department Norfolk Naval Shipyard Portsmouth, Virginia	2 U. S. Maritime Administration GAO Building 441 G Street, N. W. Washington, D. C. Attn: Division of Ship Design Division of Research
1 Commander Planning Department Charleston Naval Shipyard U. S. Naval Base Charleston, South Carolina	1 Superintendent U. S. Merchant Marine Academy Kings Point, Long Island, New York Attn: Capt. L. S. McCready (Dept. of Engineering)
1 Commander Planning Department Long Beach Naval Shipyard Long Beach 2, California	1 Commanding Officer and Director U. S. Navy Mine Defense Laboratory Panama City, Florida
1 Commander Planning Department U. S. Naval Weapons Laboratory Dahlgren, Virginia	1 Commanding Officer NROTC and Naval Administrative Unit Massachusetts Inst. of Technology Cambridge 39, Massachusetts
1 Commander U. S. Naval Ordnance Laboratory White Oak, Maryland	1 U. S. Army Transportation Research and Development Command Fort Eustis, Virginia Attn: Marine Transport Division
1 Dr. A. V. Hershey Computation and Exterior Ballistics Laboratory U. S. Naval Weapons Laboratory Dahlgren, Virginia	1 Mr. J. B. Parkinson National Aeronautics and Space Administration 1512 H Street, N. W. Washington 25, D. C.
1 Superintendent U. S. Naval Academy Annapolis, Maryland Attn: Library	2 Director Langley Research Center Langley Station Hampton, Virginia Attn: Mr. I. E. Garrick Mr. D. J. Marten
1 Superintendent U. S. Naval Postgraduate School Monterey, California	

DISTRIBUTION LIST

Copies

- | | |
|--|---|
| <p>2 Dr. G. F. Wislicenus
Ordnance Research Laboratory
Pennsylvania State University
University Park, Penna.
Attn: Dr. M. Sevik</p> <p>1 Professor R. C. DiPrima
Department of Mathematics
Rensselaer Polytechnic Institute
Troy, New York</p> <p>2 Webb Institute of Naval Arch.
Crescent Beach Road
Glen Cove, New York
Attn: Professor E. V. Lewis
Technical Library</p> <p>1 Director
Woods Hole Oceanographic Institute
Woods Hole, Massachusetts</p> <p>1 Executive Director
Air Force Office of Scientific
Research
Washington 25, D. C.
Attn: Mechanics Branch</p> <p>1 Commander
Wright Air Development Div.
Aircraft Laboratory
Wright-Patterson Air Force Base
Ohio
Attn: Mr. W. Mykytow, Dynamics</p> <p>2 Cornell Aeronautical Laboratory
4455 Genesee Street
Buffalo, New York
Attn: Mr. W. Targoff
Mr. R. White</p> <p>3 Mass. Institute of Technology
Fluid Dynamics Research Lab.
Cambridge 39, Massachusetts
Attn: Prof. H. Ashley
Prof. M. Landahl
Prof. J. Dugundji</p> <p>1 Dr. S. F. Hoerner
148 Busteed Drive
Midland Park, New Jersey</p> <p>1 Boeing Airplane Company
Seattle Division
Seattle, Washington
Attn: Mr. M. J. Turner</p> | <p>1 Electric Boat Division
General Dynamics Corporation
Groton, Connecticut
Attn: Mr. Robert McCandliss</p> <p>1 General Applied Sciences
Laboratories, Inc.
Merrick and Stewart Aves.
Westbury, L. I., N. Y.</p> <p>1 Gibbs and Cox, Inc.
21 West Street
New York, N. Y.</p> <p>3 Grumman Aircraft Eng. Corp.
Bethpage, L. I., N. Y.
Attn: Mr. E. Baird
Mr. E. Bower
Mr. W. P. Carl</p> <p>1 Lockheed Aircraft Corporation
Missiles and Space Div.
Palo Alto, California
Attn: R. W. Kermeen</p> <p>1 Midwest Research Institute
425 Volker Blvd.
Kansas City 10, Missouri
Attn: Mr. Zeydel</p> <p>3 Director, Dept. of Mech. Sciences
Southwest Research Institute
8500 Culebra Road
San Antonio 6, Texas
Attn: Dr. H. N. Abramson
Mr. G. Ransleben
Editor, Applied Mechanics
Review</p> <p>2 Convair
A Division of General Dynamics
San Diego, California
Attn: Mr. R. H. Oversmith
Mr. H. T. Brooke</p> <p>1 Hughes Tool Company
Aircraft Division
Culver City, California
Attn: Mr. M. S. Harned</p> <p>1 Hydronautics, Incorporated
Pindell School Road
Howard County
Laurel, Maryland
Attn: Mr. Phillip Eisenberg</p> |
|--|---|

DISTRIBUTION LIST

Copies

- | | | | |
|---|---|---|---|
| 1 | Rand Development Corporation
13600 Deise Avenue
Cleveland 10, Ohio
Attn: Dr. A. S. Iberall | 2 | Stanford University
Dept. of Civil Engineering
Stanford, California
Attn: Dr. Byrne Perry
Dr. E. Y. Hsu |
| 1 | U. S. Rubber Company
Research and Development Dept.
Wayne, New Jersey
Attn: Mr. L. M. White | 1 | Dr. Hirsh Cohen
IBM Research Center
P. O. Box 218
Yorktown Heights, New York |
| 1 | Technical Research Group, Inc.
2 Aerial Way
Syosset, L. I., N. Y.
Attn: Dr. Jack Kotik | 1 | Mr. David Wellinger
Hydrofoil Projects
Radio Corporation of America
Burlington, Massachusetts |
| 1 | AVCO Corporation
Lycoming Division
1701 K Street, N. W., Apt. 904
Washington, D. C.
Attn: Mr. T. A. Duncan | 1 | Food Machinery Corporation
P. O. Box 367
San Jose, California
Attn: Mr. G. Tedrew |
| 1 | Mr. J. G. Baker
Baker Manufacturing Company
Evansville, Wisconsin | 1 | Dr. T. R. Goodman
Oceanics, Inc.
Technical Industrial Park
Plainview, L. I., N. Y. |
| 1 | Curtiss-Wright Corp. Research Div.
Turbomachinery Division
Quehanna, Pennsylvania
Attn: Mr. George Pedersen | 1 | Professor Brunelle
Dept. of Aeronautical Engineering
Princeton University
Princeton, New Jersey |
| 1 | Dr. Blaine R. Parkin
AirResearch Manufacturing Corp.
9851-9951 Sepulveda Blvd.
Los Angeles 45, California | 1 | Commanding Officer
Office of Naval Research Br Ofc
86 East Randolph Street
Chicago 1, Illinois |
| 1 | The Boeing Company
Aero-Space Division
Seattle 24, Washington
Attn: Mr. R. E. Bateman
(Internal Mail Station 46-74) | 1 | The Rand Corporation
1700 Main Street
Santa Monica, California
Attn: Technical Library |
| 1 | Lockheed Aircraft Corporation
California Division
Hydrodynamics Research
Burbank, California
Attn: Mr. Bill East | 1 | National Research Council
Montreal Road
Ottawa 2, Canada
Attn: Mr. E. S. Turner |
| 1 | Mass. Institute of Technology
Dept. of Naval Architecture and
Marine Engineering
Cambridge 39, Massachusetts
Attn: Prof. M. A. Abkowitz | | |

DISTRIBUTION LIST

Copies

16 Commanding Officer and Director David Taylor Model Basin Washington 7, D. C. Attn: Codes 108 142 500 513 520 525 526 526A 530 533 580 585 589 591 591A 700	3 Versuchsanstalt für Wasserbau und Schiffbau Schleuseninsel im Tiergarten Berlin, Germany Attn: Dr. S. Schuster, Director Dr. H. Schwanecke Dr. Grosse
	1 Technische Hogeschool Institut voor Toegepaste Wiskunde Julianalaan 132 Delft, Netherlands Attn: Prof. R. Timman
	1 Bureau D'Analyse et de Recherche Appliquees 47 Avenue Victor Cresson Issy-Les-Moulineaux Seine, France Attn: Prof. Siestrunck
1 Hamburgische Schiffbau-Versuchsanstalt Bramfelder Strasse 164 Hamburg 33, Germany Attn: Dr. H. W. Lerbs	1 Netherlands Ship Model Basin Wageningen, The Netherlands Attn: Dr. Ir. J. D. van Manen
1 Institut für Schiffbau der Universität Hamburg Berliner Tor 21 Hamburg 1, Germany Attn: Dr. O. Grim	2 National Physical Laboratory Teddington, Middlesex, England Attn: Mr. A. Silverlead Head, Aerodynamics Div.
1 Trans. Technical Research Inst. 1-1057, Mejiro-Cho, Toshima-Ku Tokyo, Japan	2 Head, Aerodynamics Department Royal Aircraft Establishment Farnborough, Hants, England Attn: Mr. M. O. W. Wolfe
1 Max-Planck Institut für Strömungsforschung Bottingerstrasse 6/8 Gottingen, Germany Attn: Dr. H. Reichardt	1 Skipsmodelltanken Trondheim, Norway Attn: Professor J. K. Lunde
1 Hydro-og Aerodynamisk Laboratorium Lyngby, Denmark Attn: Prof. Carl Prohaska	1 Mr. C. Wigley Flat 102 6-9 Charterhouse Square London E.C.1 England

WAVE-RESISTANCE REDUCTION
OF NEAR-SURFACE BODIES

by King Eng and Pung M. Hu, March 1963

Davidson Laboratory Report No. 933
UNCLASSIFIED

An analytical study of the wave-resistance characteristics of near-surface bodies was conducted to determine 1) for a given length and displacement, what changes in body-surface geometry are necessary to cause wave-resistance reduction, and 2) how geometrical change affects the wave-resistance behavior with Froude number and submergence depth. The general wave-resistance expression for a perturbed ellipsoid with the constraints of constant displacement and length is formulated. A digital computer solution of this variational problem is obtained for the case of the spheroid due to available computer-size limitations.

The effects of fineness ratio and submergence-to-length ratio on the Froude number behavior of the wave resistance for a range of perturbations is demonstrated. Substantial reduction in wave resistance is possible for all Froude numbers above and slightly below the optimum Froude number for a particular perturbation distribution. For Froude numbers lower than approximately 10% below the optimum Froude number, a large increase in wave-resistance coefficient may be obtained depending upon the perturbation used. Since this generally occurs at low Froude numbers, the actual increase in total resistance experienced for perturbations yielding acceptable geometrical changes should be quite acceptable. Depending upon the optimum Froude number, the geometrical changes required for wave-resistance reduction fall into two classes:

- 1) midsection bulge with finer bow and stern for Froude numbers below 0.32;
- and 2) above 0.32 Froude number a midsection pinch with bulging bow and stern.

WAVE-RESISTANCE REDUCTION
OF NEAR-SURFACE BODIES

by King Eng and Pung M. Hu, March 1963

Davidson Laboratory Report No. 933
UNCLASSIFIED

An analytical study of the wave-resistance characteristics of near-surface bodies was conducted to determine 1) for a given length and displacement, what changes in body-surface geometry are necessary to cause wave-resistance reduction, and 2) how geometrical change affects the wave-resistance behavior with Froude number and submergence depth. The general wave-resistance expression for a perturbed ellipsoid with the constraints of constant displacement and length is formulated. A digital computer solution of this variational problem is obtained for the case of the spheroid due to available computer-size limitations.

The effects of fineness ratio and submergence-to-length ratio on the Froude number behavior of the wave resistance for a range of perturbations is demonstrated. Substantial reduction in wave resistance is possible for all Froude numbers above and slightly below the optimum Froude number for a particular perturbation distribution. For Froude numbers lower than approximately 10% below the optimum Froude number, a large increase in wave-resistance coefficient may be obtained depending upon the perturbation used. Since this generally occurs at low Froude numbers, the actual increase in total resistance experienced for perturbations yielding acceptable geometrical changes should be quite acceptable. Depending upon the optimum Froude number, the geometrical changes required for wave-resistance reduction fall into two classes:

- 1) midsection bulge with finer bow and stern for Froude numbers below 0.32;
- and 2) above 0.32 Froude number a midsection pinch with bulging bow and stern.

WAVE-RESISTANCE REDUCTION
OF NEAR-SURFACE BODIES

by King Eng and Pung M. Hu, March 1963

Davidson Laboratory Report No. 933
UNCLASSIFIED

An analytical study of the wave-resistance characteristics of near-surface bodies was conducted to determine 1) for a given length and displacement, what changes in body-surface geometry are necessary to cause wave-resistance reduction, and 2) how geometrical change affects the wave-resistance behavior with Froude number and submergence depth. The general wave-resistance expression for a perturbed ellipsoid with the constraints of constant displacement and length is formulated. A digital computer solution of this variational problem is obtained for the case of the spheroid due to available computer-size limitations.

The effects of fineness ratio and submergence-to-length ratio on the Froude number behavior of the wave resistance for a range of perturbations is demonstrated. Substantial reduction in wave resistance is possible for all Froude numbers above and slightly below the optimum Froude number for a particular perturbation distribution. For Froude numbers lower than approximately 10% below the optimum Froude number, a large increase in wave-resistance coefficient may be obtained depending upon the perturbation used. Since this generally occurs at low Froude numbers, the actual increase in total resistance experienced for perturbations yielding acceptable geometrical changes should be quite acceptable. Depending upon the optimum Froude number, the geometrical changes required for wave-resistance reduction fall into two classes:

- 1) midsection bulge with finer bow and stern for Froude numbers below 0.32;
- and 2) above 0.32 Froude number a midsection pinch with bulging bow and stern.

WAVE-RESISTANCE REDUCTION
OF NEAR-SURFACE BODIES

by King Eng and Pung M. Hu, March 1963

Davidson Laboratory Report No. 933
UNCLASSIFIED

An analytical study of the wave-resistance characteristics of near-surface bodies was conducted to determine 1) for a given length and displacement, what changes in body-surface geometry are necessary to cause wave-resistance reduction, and 2) how geometrical change affects the wave-resistance behavior with Froude number and submergence depth. The general wave-resistance expression for a perturbed ellipsoid with the constraints of constant displacement and length is formulated. A digital computer solution of this variational problem is obtained for the case of the spheroid due to available computer-size limitations.

The effects of fineness ratio and submergence-to-length ratio on the Froude number behavior of the wave resistance for a range of perturbations is demonstrated. Substantial reduction in wave resistance is possible for all Froude numbers above and slightly below the optimum Froude number for a particular perturbation distribution. For Froude numbers lower than approximately 10% below the optimum Froude number, a large increase in wave-resistance coefficient may be obtained depending upon the perturbation used. Since this generally occurs at low Froude numbers, the actual increase in total resistance experienced for perturbations yielding acceptable geometrical changes should be quite acceptable. Depending upon the optimum Froude number, the geometrical changes required for wave-resistance reduction fall into two classes:

- 1) midsection bulge with finer bow and stern for Froude numbers below 0.32;
- and 2) above 0.32 Froude number a midsection pinch with bulging bow and stern.